

Abden

Backlit LED panel with emergency option

- Save up to 50% energy usage compared to traditional fluorescent fittings
 - TP(a) rated diffuser
- Square edge tray with robust structure to allow even light distribution around the edge
- DALI, 1-10V (0-10V) and PUSH alternative driver available
 - IP44 when ceiling recess mounted
 - Flicker free
 - UGR<19

Plug-in emergency 

Flicker free 

CHIP **OSRAM** LUMILEDS
DRIVER **PHILIPS** LIFUD®



3 Years Standard Warranty

5 Years Extended Warranty

1000V Surge Protection

DALI & 1-10V (0-10V) Dimmable Options

New Optional Gear



Standard/Self-test universal emergency module



Optional Connector ECON3FM

Order Code	Power	Dimension	CCT	Lumen	Trade Price
EPNL30BL1	30W	595x595	3000K 4000K 6500K	3200lm	

Optional Gears

Type	Order Code	Description	Trade Price
Dimmable driver	EYC030TDC30-90	Configurable DALI & 1-10V (0-10V) Dimmable Driver	
Emergency module	EEW03LIL/N	UEM, 3W, Li-ion battery	
Self-test emergency module	EEW03LIL/S	Self-test UEM, 3W, Li-ion battery	

Accessories

Type	Order Code	Description	Trade Price
Surface mount frame	EPTPNL/SMT-WHT0606	595x595mm surface-mount frame, white	
Suspension kits	EPTPNL/SUS0606	595*595mm Suspension set	
Connector	ECON3FM	Junction Box Connector - 3 Pin + Loop	

General Specification

Voltage 220-240Vac
50-60Hz
CRI >83
Life Time 50,000h
Power Factor >0.95
Ambient Temp -20°C to 45°C
Housing Powder coated aluminum
Diffuser Polystyrene TP(a)



Dimensions

