

5 5 Years
Standard Warranty

7 7 Years
Extended Warranty

1000V
Surge Protection

DALI & 1-10V (0-10V)
Dimmable Options

New Optional Gear



General Specification

Voltage 220-240Vac
50-60Hz
CRI >80
Life Time 50,000h
Power Factor >0.90
Ambient Temp -20°C to 45°C
Housing Powder coated aluminum
Diffuser Polystyrene TP(a)



Bali

Premium LED panels

- Save up to 70% energy usage compared to traditional fluorescent fittings
- Ultra-low glare, UGR<17*
- TP(a) fire resistant diffuser
- Flicker free
- Optional DALI, 1-10V (0-10V) driver
- IP44 when ceiling recess mounted
- White powder coated aluminium frame

- ➔ Plug-in emergency
- ➔ Plug-in on/off sensor
- Watt Wattage switching
- 🌿 Flicker free
- 🌿 Modular design
- 🌿 Ultra high efficiency



CHIP **OSRAM** LUMILEDS
DRIVER **PHILIPS** LIFUD®

Ultra-Low Glare (UGR<17*)

Order Code	Default Power	Alternative Power	Dimension	CCT	Lumen	Trade Price
ELED3627PNL	36W	-	595x595mm	4000K	4000lm	
				6500K		
	-	27W	595x595mm	4000K	3100lm	
				6500K		

Highly Efficient (>130lm/w)

Order Code	Default Power	Alternative Power	Dimension	CCT	Lumen	Trade Price
ELED2328PNL	23W	-	595x595mm	4000K	3000lm	
				6500K		
	-	28W	595x595mm	4000K	3400lm	
				6500K		

Dimensions

