

Bali-Standard

(595 x 595mm)

Flicker free LED panels for schools and offices

Plug-in emergency 

Plug-in on/off sensor 

Flicker free 

Modular design 

- Save up to 60% energy usage compared to traditional fluorescent fittings
 - Low glare, UGR<19*
- TP(b) fire resistant polycarbonate diffuser
 - Flicker free
- Optional DALI, 1-10V (0-10V) driver
- IP44 when ceiling recess mounted
- White powder coated aluminium frame

CHIP **OSRAM** LUMILEDS
DRIVER **PHILIPS** LIFUD®



5 5 Years Standard Warranty

7 7 Years Extended Warranty

1000V Surge Protection

DALI & 1-10V (0-10V) Dimmable Options

New Optional Gear



General Specification

Voltage	220-240Vac 50-60Hz
CRI	>80
Life Time	50,000h
Power Factor	>0.95
Ambient Temp	-20°C to 45°C
Housing	Powder coated aluminum
Diffuser	Polycarbonate TP(b)



Order Code	Power	Dimension	CCT	Lumen	Trade Price
ELED40PNL	40W	595x595mm	4000K 6500K	4200lm	

Optional Gears

Type	Order Code	Description	Trade Price
Dimmable driver	EYC050TDC70-140	(0-10V) Dimmable	
Emergency module	EEW03LIL/N	UEM, 3W, Li-ion battery	
Self-test emergency module	EEW03LIL/S	Self-test UEM, 3W, Li-ion battery	
Presence sensor	EYS-PRS-PNL	On/off presence sensor dedicated to LED panel	
Daylight harvesting	EYS50DLH-PNL	Daylight harvesting control unit	

Accessories

Type	Order Code	Description	Trade Price
Surface mount frame	EPTPNL/SMT-WHT0606	595x595mm surface-mount frame, white	
Suspension kits	EPTPNL/SUS0606	595x595mm Suspension set	
Connector	ECON3FM	Junction Box Connector - 3 Pin + Loop	

* With room size of 4h x 2h, where h is the height of the room

Dimensions

