

Twin Bar

Ceiling luminaire with two parallel edge-lit LED panels

Plug-in emergency 

Plug-in on/off sensor 

Wattage switching 

Flicker free 

Modular design 

- Save up to 60% energy usage compared to traditional fluorescent fittings
 - Low glare, UGR<19*
- TP(b) fire resistant polycarbonate diffuser
 - Flicker free
- Optional DALI, 1-10V (0-10V) driver
- White powder coated aluminium frame

CHIP **OSRAM** LUMILEDS
DRIVER **PHILIPS** **LIFUD**



5 5 Years Standard Warranty

7 7 Years Extended Warranty

1000V Surge Protection

DALI & 1-10V (0-10V) Dimmable Options

New Optional Gear



Dimmable LED driver with integrated sensor



Optional Connector ECON3FM

General Specification

Voltage	220-240Vac 50-60Hz
CRI	>80
Life Time	50,000h
Power Factor	>0.93
Ambient Temp	-20°C to 45°C
Housing	Powder coated aluminum
Diffuser	Polycarbonate TP(b)



Order Code	Default Power	Alternative Power	Dimension	CCT	Lumen	Trade Price
ETWB3040PNL	30W	-	595x595mm	4000K	3200lm	
	-	40W	595x595mm	6500K 4000K 6500K	4200lm	

Optional Gears

Type	Order Code	Description	Trade Price
Dimmable driver	EY050TDC70-140	(0-10V) Dimmable Driver	
Emergency module	EEW03LIL/N	UEM, 3W, Li-ion battery	
Self-test emergency module	EEW03LIL/S	Self-test UEM, 3W, Li-ion battery	
Presence sensor	EYS-PRS-PNL	On/off presence sensor dedicated to LED panel	

Accessories

Type	Order Code	Description	Trade Price
Surface mount frame	EPTPNL/SMT-WHT0606	595x595mm surface-mount frame, white	
Suspension kits	EPTPNL/SUS0606	595x595mm Suspension set	
Connector	ECON3FM	Junction Box Connector - 3 Pin + Loop	

* With room size of 4h x 2h, where h is the height of the room

Dimensions

