

Curve

Direct / indirect LED modular Luminaire

- Stylish & elegant aesthetic appearance
 - Flicker free
 - Ultra-low glare, UGR<17.4*
- Optional DALI, 1-10V (0-10V) driver
- Colour temperature switchable 3000K/4000K/5000K

Plug-in emergency 

Wattage switching 

CCT switching 

Flicker free 

CHIP **OSRAM** LUMILEDS
DRIVER **PHILIPS** LiFiD®



- 5** 5 Years Standard Warranty
- 7** 7 Years Extended Warranty
- 1000V** Surge Protection
- DALI & 1-10V (0-10V)** Dimmable Options

General Specification

Voltage 220-240Vac
50-60Hz
CRI >80
Life Time 50,000h
Power Factor >0.93
Ambient Temp -20°C to 45°C
Housing Zinc coated sheet steel
Diffuser Acrylic



Order Code	Default Power	Alternative Power	Dimension	CCT	Lumen	Trade Price
EMRC4030L2A	40W	-	595x595mm	Switchable**	3600lm	
	-	30W	595x595mm	Switchable**	2800lm	

Optional Gears

Type	Order Code	Description	Trade Price
Dimmable driver	EC050TDC70-140		
Emergency module	EEW03LIL/N	UEM, 3W, Li-ion battery	
Self-test emergency module	EEW03LIL/S	Self-test UEM, 3W, Li-ion battery	

* With room size of 4h x 2h, where h is the height of the room

Dimensions

