







- Built-in emergency 
- Plug-in self-test EM 
- Built-in motion sensor 
- CCT switching 
- Flicker free 
- Modular design 

Keola

Large ultra slim LED bulkhead

- Diameter of 300mm & 330mm
- IP20 and IP40 options IK 08
- Option of base with emergency module
- Integrated LED board for uniform light output
- High lumen output of up to 4000lm

- 5** 5 Years Standard Warranty
- 7** 7 Years Extended Warranty
- 1000V** Surge Protection
- Mains Dimmable** Dimmable

CHIP **OSRAM** LUMILEDS
DRIVER **PHILIPS** LIFUD



General Specification

Voltage 220-240Vac
50-60Hz
CRI 84
Life Time 50000h
Power Factor >0.85
Ambient Temp -20°C to 45°C
Housing Polycarbonate



Order Code	Description	Trade Price
EBHGT25	Dimmable, 320mm diameter, Class II, IP20, IK08, 25W, 3000K/4000K/5000K, 2500lm	
EBHGT25SCT	Sensor, 320mm diameter, Class II, IP20, IK08, 25W, Switchable 3000K/4000K/5000K, 2600lm	
EBHGT40	Dimmable, 320mm diameter, Class II, IP20, IK08, 40W, 3000K/4000K/5000K, 3900lm	
EBHGT40CSCT	Sensor, 320mm diameter, Class II, IP20, IK08, 40W, Switchable 3000K/4000K/5000K, 4000lm	

Emergency Option

Suffix	Description	Trade Price
/E	Emergency with Li-ion battery	

Battery

Order Code	Type	Capacity	Voltage	Trade Price
EBAT2600	Li-ion	2600mAh	7.4V	

Optional Gear

Type	Order Code	Description	Trade Price
Self-test Emergency module	EEC03LBL/S	Self-test emergency module, Li-ion battery	

Dimensions

