

5 5 Years
Standard Warranty

7 7 Years
Extended Warranty

2000V
Surge Protection
(L-to GND)

Kodale

Surface or pendant LED circular panel

- Choices of 400mm, 500mm, 600mm diameter
- Emergency and microwave sensor options
- Surface or suspension mounting
- Flicker free

 Built-in emergency

 Built-in motion sensor

 Flicker free

CHIP **OSRAM** LUMILEDS
DRIVER **PHILIPS** LIFUD






General Specification

Voltage 220-240Vac
50-60Hz
CRI >80
Life Time 50,000h
Power Factor >0.95
Ambient Temp -20°C to 45°C
Housing Anodized aluminum
Diffuser Polycarbonate



Dimensions



Front LED panel (Must be ordered with back box)

Order Code	Power	Input Current	CCT	Lumen	Trade Price
EPNLLS25CS	25W	710mA	4000K	2100lm	
EPNLLS30CS	30W	710mA	4000K	2200lm	
EPNLLS35CS	35W	710mA	4000K	2940lm	

Back Box (Must be ordered with front LED panel)

Order Code	Type	Output Current	Battery	Trade Price
EPNLLS-BB	Standard	710mA	/	

Options

Suffix	Description	Trade Price
/E	Emergency with Li-ion battery	
/S	Microwave sensor	
/ES	Emergency & Microwave sensor	

Battery

Order Code	Type	Capacity	Voltage	Trade Price
EBAT2600	Li-ion	2600mAh	7.4V	

Accessory

Type	Order Code	Description	Trade Price
Suspension kits	EPNLLS-SUS	Mounting plate with three wires. Up to 0.8m drop	