



**3** 3 Years  
Standard Warranty

**5** 5 Years  
Extended Warranty

**2000V**  
Surge Protection  
(L to GND)

**General Specification**

Voltage 220-240Vac  
50-60Hz  
CRI >80  
Life Time 50,000h  
Power Factor 0.95  
Ambient Temp -20°C to 45°C  
Housing Polycarbonate



# Rashi

Interior batten with integrated LED

- Retrofit replacement of traditional T8 single and twin battens
- Option of integrated emergency version
- Option of reflectors
- BESA box fitting points

Built-in emergency


Ultra high efficiency

CHIP OSRAM LUMILEDS  
DRIVER PHILIPS LIFUD



Order Code	Power	Length	CCT	Lumen	Trade Price
EBTN20LS7	20W	2ft	4000K	2400lm	
EBTN40LS7	40W	4ft	4000K	4600lm	
EBTN60LS7	60W	5ft	4000K	6800lm	
EBTN80LS7	80W	6ft	4000K	8800lm	

**Dimensions**



**Emergency Option**

Suffix	Description	Trade Price
/E	Emergency with Li-ion battery	

**Battery**

Order Code	Type	Capacity	Voltage	Trade Price
EBAT2200LI3	Li-ion	2200mAh	7.4V	