

3 3 Years
 Standard Warranty

5 5 Years
 Extended Warranty

⚡ 1000V
 Surge Protection

General Specification

Voltage 220-240Vac
 50-60Hz
 CRI >80
 Life Time 50,000h
 Power Factor >0.53
 Ambient Temp -20°C to 45°C
 Housing Polycarbonate



Arno

Thin profile interior batten with integrated LED

- High efficiency of 110lm/W
- 2 ranges for replacement of single and twin T8 battens
- Supplied with long lead of 2/3 length of the luminaire

CHIP **OSRAM** **LUMILEDS**
 DRIVER **PHILIPS** **LIFUD**


Dimensions

Single Output (with light output of single T8 batten)

Order Code	Power	Length	CCT	Lumen	Trade Price
EBTN12LS5	12W	2ft	4000K 6500K	1320lm	
EBTN18LS5	18W	4ft	4000K 6500K	1980lm	
EBTN36LS5	36W	5ft	4000K 6500K	3960lm	
EBTN45LS5	45W	6ft	4000K 6500K	4950lm	

Twin Output (with light output of twin T8 batten)

Order Code	Power	Length	CCT	Lumen	Trade Price
EBTN18LS6	18W	2ft	4000K 6500K	1980lm	
EBTN30LS6	30W	4ft	4000K 6500K	3520lm	
EBTN48LS6	48W	5ft	4000K 6500K	5280lm	
EBTN60LS6	60W	6ft	4000K 6500K	6600lm	