

Arno-Pro

Wattage and CCT switchable interior LED batten

Plug-in corridor sensor 

CCT switching 

Wattage switching 

Modular design 

Ultra high efficiency 

CHIP **OSRAM** **LUMILEDS**
DRIVER **PHILIPS** **LIFUD**

- High efficiency of 120lm/W
- Switchable CCT (3000K/4000K/6000K)
 - 2 switchable wattage
- Easy installation with surface mounting clips
 - Plug-in motion sensor
 - BESA box fitting points



Sensor



Microwave Sensor
(Mounting height ≤8.5m)
EBTNLS1-MWS2

General Specification

Voltage 220-240Vac
50-60Hz
CRI >80
Life Time 50,000h
Power Factor >0.90
Ambient Temp -20°C to 45°C
Housing Polycarbonate



Order Code	Default Power	Alternative Power	Length	CCT	Lumen	Trade Price
EBTN1832LS15	-	18W	4ft	Switchable*	1980lm(3000K) 2160lm(4000K) 2160lm(6000K)	
	32W	-	4ft	Switchable*	3520lm(3000K) 3840lm(4000K) 3840lm(6000K)	
EBTN3648LS15	-	36W	5ft	Switchable*	3960lm(3000K) 4320lm(4000K) 4320lm(6000K)	
	48W	-	5ft	Switchable*	5280lm(3000K) 5760lm(4000K) 5760lm(6000K)	

* When CCT switchable, colour temperature switches 3000K, 4000K & 6000K

Options Gear

Type	Order code	Description	Trade Price
Microwave Sensor	EBTNLS1-MWS2	Microwave motion and daylight sensor	

Dimensions

