

Slimmy

Slim profile integrated LED batten

- Switchable CCT (3000K/4000K/6000K) for Slim-Line II
 - High efficiency of 120 lm/W
 - Slim profile
- Simple external bracket mounting
- Long operational life of 40,000 h

CCT switching 

Flicker free 

Ultra high efficiency 

CHIP **OSRAM**  **LUMILEDS**

DRIVER **PHILIPS**  **LIFUD**



Suspension mount



General Specification

Voltage	220-240Vac
	50-60Hz
CRI	>80
Life Time	50,000h
Power Factor	0.95
Ambient Temp	-20°C to 45°C
Housing	Polycarbonate



Slim-Line II

Order Code	Power	Length	CCT	Lumen	Trade Price
EBTN30LS2/SCT	30W	4ft	Switchable*	3600lm (3000K)	
				3800lm (4000K)	
				3800lm (6000K)	
EBTN45LS2/SCT	45W	5ft	Switchable*	5400lm (3000K)	
				5600lm (4000K)	
				5600lm (6000K)	

* When CCT switchable, colour temperature switches between 3000K, 4000K & 6000K

Slim-Line I

Order Code	Power	Length	CCT	Lumen	Trade Price
EBTNHS30LS2	30W	4ft	4000K	3800lm	
EBTNHS45LS2	45W	5ft	4000K	5500lm	

Accessory

Type	Order Code	Description	Trade Price
Suspension Kit	EPTBTN/SUS2	Maximum 1.3m drop	

Dimensions

