

Rilo

Interior batten with edge-lit LED panel

- Designed to replace the popular twin T8 surface modular
 - Switchable wattage
 - Flicker-free driver as standard
- Daylight harvesting alternative driver available
 - Plug & play microwave sensor module
 - Plug & play emergency module
 - BESA box fitting points

Plug-in emergency 

Plug-in on/off sensor 

Wattage switching 

Flicker free 

Modular design 

CHIP **OSRAM** LUMILEDS
DRIVER **PHILIPS** LIFUD



Order Code	Default Power	Alternative Power	Length	CCT	Lumen	Trade Price
EBTN2328LS9	23W	-	4ft	4000K	2500lm	
	-	28W	4ft	4000K	2800lm	
EBTN3040LS9	30W	-	5ft	4000K	3000lm	
	-	40W	5ft	4000K	4000lm	

Optional Gears

Type	Order Code	Description	Trade Price
Dimmable driver	EYC030TDC30-90	Configurable DALI & 1-10V (0-10V) Dimmable Driver for KBTN2328LS9	
Dimmable driver	EYC050TDC70-140	Configurable DALI & 1-10V (0-10V) Dimmable Driver for KBTN3040LS9	
Daylight harvesting	EYS50DLH-PNL	Daylight Harvesting Driver	
Emergency module	EEW03LIL/N	UEM, 3W, Li-ion battery	
Self-test emergency module	EEW03LIL/S	Self-test UEM, 3W, Li-ion battery	
Presence sensor	EYS-PRS-PNL	On/off presence sensor dedicated to LED panel	

Accessory

Type	Order Code	Description	Trade Price
Suspension Kit	EPTBTN/SUS3	Maximum 1.0m drop	

5 5 Years Standard Warranty

7 7 Years Extended Warranty

DALI & 1-10V (0-10V) Dimmable Options

1000V Surge Protection

New Optional Gear



Dimmable LED driver with integrated sensor

Surface-mount



Suspension mount



General Specification

Voltage 220-240Vac
50-60Hz
CRI >80
Life Time 50,000h
Power Factor 0.90
Ambient Temp -20°C to 45°C
Housing Polycarbonate

