

Poba

Wattage and CCT switchable Ultra slim profile circular LED surface luminaire with mounting options

Wattage switching



CCT switching



CHIP OSRAM LUMILEDS

- Surface or cut-out mounting options
- Ultra slim profile of only 21.5mm / 25mm
- IP44, suitable for bathroom applications
 - Switchable CCT 3000K/4000K/6500K
- Unique adjustable mounting bracket (cut-out range 65-205mm)
 - Long life of 40,000hrs
 - IP44, Class II



3 Years Standard Warranty

5 Years Extended Warranty

65-205mm Cut-out

500V Surge Protection



Surface mount



Recessed mount

General Specification

Voltage 220-240Vac
50-60Hz
CRI >80
Life Time 50,000h
Power Factor 0.93
Ambient Temp -20°C to 45°C
Housing Polycarbonate
Diffuser Polystyrene



Order Code	Default Power	Alternative Power	Beam Angle	Cut-out	CCT	Lumen	Trade Price
EPNL08S1	-	8W	120°	75-80mm	Switchable*	800lm(3000K) 8100lm(4000K) 8100lm(6500K)	
EPNL12S1	-	12W	120°	90-100mm	Switchable*	1200lm(3000K) 1250lm(4000K) 1250lm(6500K)	
EPNL20S1		20W	120°	155-165mm	4000K	1900lm	
EPNL30S1		30W	120°	195-205mm	Switchable*	2950lm(3000K) 3000lm(4000K) 3000lm(6500K)	

* When CCT switchable, colour temperature switches between 3000K, 4000K & 6500K

Dimensions

