

5 5 Years
Standard Warranty

7 7 Years
Extended Warranty

500V
Surge Protection

DALI & 1-10V (0-10V)
Dimmable Options

140/160/227mm
Cut-out

New Optional Gear



Standard/Self-test universal emergency module

General Specification

Voltage 220-240Vac
50-60Hz
CRI 82
Life Time 50,000h
Power Factor >0.90
Ambient Temp -20°C to 45°C
Housing Diecast aluminum
Diffuser Polycarbonate



Dimensions



Cyos

Edge-lit circular LED panel downlight

- IP20 when ceiling recess mounted
- Ultra-slim profile
- Flicker free
- Optional DALI, 1-10V (0-10V) driver

Plug-in emergency

Flicker free

Modular design

CHIP OSRAM LUMILEDS
DRIVER PHILIPS LIFUD



Order Code	Power	Beam Angle	Cut-out	CCT	Lumen	Trade Price
EPNLLS5CF	5W	110°	75mm	3000K 4000K 6500K	510lm	
EPNLLS7CF	7W	110°	85mm	3000K 4000K 6500K	700lm	
EPNLLS9CF	9W	110°	95mm	3000K 4000K 6500K	950lm	
EPNLLS12CF	12W	110°	120mm	3000K 4000K 6500K	1210lm	
EPNLLS18CF	18W	110°	145mm	3000K 4000K 6500K	1900lm	
EPNLLS24CF	24W	110°	170mm	3000K 4000K 6500K	2350lm	
EPNLLS30CF	30W	110°	190mm	3000K 4000K 6500K	2950lm	