

Pacata

Premium LED downlight with faceted reflector

Plug-in emergency 

CCT switching 

Wattage switching 

Flicker free 

Modular design 

CHIP **OSRAM** LUMILEDS
DRIVER **PHILIPS** LIFUD®

- IP44 when ceiling recess mounted
- Unique faceted white reflector
- Optional drop-down diffusers
 - Low glare
 - Flicker free
- Optional DALI, 1-10V (0-10V) driver (KC DL2622FR65)
 - Option of CCT switching 3000K, 4000K, 5000K



5 5 Years
Standard Warranty

7 7 Years
Extended Warranty

1000V
Surge Protection

DALI & 1-10V (0-10V)
Dimmable Options

**86/111/164/
215mm**
Cut-out

New Optional Gear



Standard/Self-test
universal emergency module



In-line switch for
CCT selection

General Specification


Voltage 220-240Vac
50-60Hz
CRI 85
Life Time 50,000h
Power Factor >0.90
Ambient Temp -20°C to 45°C
Housing PBT
Diffuser Polycarbonate




Order Code	Power	Beam Angle	Cut-out	CCT	Lumen
EDLLS12FR44	12W	15/24 38/55°	110mm	Switchable*	1150lm(3000K) 1200lm(4000K) 1200lm(5000K)

* Where CCT switchable, colour temperature switches between 3000K, 4000K & 5000K


Dimensions



EDLLS12FR44



EDLLS18FR44



EDLLS24FR44

Order Code	Power	Beam Angle	Cut-out	CCT	Lumen
EDLLS18FR44	18W	15/24 38/55°	145mm	Switchable*	1750lm(3000K)
					1800lm(4000K)
					1800lm(5000K)
EDLLS24FR44	24W	15/24 38/55°	160mm	Switchable*	2350lm(3000K)
					2400lm(4000K)
					2400lm(5000K)

Optional Gears

Type	Order Code	Description	Trade Price
Dimmable driver	EYC030TDC30-90	Configurable DALI & 1-10V (0-10V) Dimmable Driver for ECDL2622FR65	
Emergency module	EEW03LIL/N	UEM, 3W, Li-ion battery	
Self-test emergency module	EEW03LIL/S	Self-test UEM, 3W, Li-ion battery	

Accessories

Type	Order Code	Description	Trade Price
Diffuser	EPT-CLR-CDL24	Clear frosted anti-glare halo diffuser for ECDL2622FR65	
Diffuser	EPT-OPL-CDL24	Opal frosted anti-glare halo diffuser for ECDL2622FR65	