

- 5** 5 Years Standard Warranty
- 7** 7 Years Extended Warranty
- Mains Dimmable** Dimmable
- 150/200mm** Cut-out
- 1000V/2000V** Surge Protection (L to GND)

# Papa

IP44 LED commercial downlight with emergency option

- Integrated dimmable driver
- Switchable CCT (3000K/4000K/6000K)
- Compatible with mains emergency module
- Optional silver and polished chrome reflectors
- High lumen output
- Long life of 40,000h
- Low glare, UGR<22

- CCT switching
- Plug-in emergency
- Flicker free
- Modular design

CHIP **OSRAM** **LUMILEDS**  
DRIVER **PHILIPS** **LIFUD**

## General Specification

Voltage 220-240Vac  
50-60Hz  
CRI >80  
Life Time 50,000h  
Power Factor 0.94  
Ambient Temp -20°C to 45°C  
Housing Zinc coated sheet steel



## Dimensions



EDL10FR44



EDL18FR44



EDL30FR44



EDL40FR44



Order Code	Power	Beam Angle	Cut-out	CCT	Lumen	Trade Price
EDL10FR44	10W	15/24 38/55°	75mm	Switchable*	800lm(3000K) 900lm(4000K) 900lm(6000K)	
EDL18FR44	18W	15/24 38/55°	90mm	Switchable*	2000lm(3000K) 2100lm(4000K) 2100lm(6000K)	
EDL30FR44	30W	15/24 38/55°	125mm	Switchable*	2800lm(3000K) 3000lm(4000K) 3000lm(6000K)	
EDL40FR44	40W	15/24 38/55°	165mm	Switchable*	3700lm(3000K) 4000lm(4000K) 4000lm(6000K)	

\* See datasheet for recommended number of lamps per dimmer