

# Lathe

Modular system of LED retail downlights

Modular design 

CHIP **OSRAM** **LUMILEDS**  
 DRIVER **PHILIPS** **LIFUD**

- Modular design of LED engine and housings
  - High performance CREE COB LED
  - Negligible UV, ideal for retail application

**5** 5 Years  
Standard Warranty

**7** 7 Years  
Extended Warranty

**500V**  
Surge Protection

**55/75/95mm**  
Cut-out



## General Specification

Voltage 220-240Vac  
50-60Hz  
 CRI >80  
 Life Time 50,000h  
 Power Factor >0.95  
 Ambient Temp -20°C to 45°C  
 Housing Diecast aluminum



Order Code	Power	Beam Angle	Finish	CCT	Lumen	Dimensions $\phi$ H
EDLLA5	5W	15/24/38°	White	6000K	<b>500lm</b>	$\phi$ 62*75mm
EDLLA10	10W	15/24/38°	White	6000K	<b>1000lm</b>	$\phi$ 85*89mm
EDLLA15	15W	15/24/38°	White	6000K	<b>1500lm</b>	$\phi$ 104*115mm
EDLLA20	20W	15/24/38°	White	6000K	<b>2000lm</b>	$\phi$ 104*115mm

## Dimensions

