

# Dies

Modular system of LED retail downlights

Modular design 

CHIP **OSRAM** **LUMILEDS**  
 DRIVER **PHILIPS** **LIFUD**

- Modular design of LED engine and housings
  - High performance CREE COB LED
  - Negligible UV, ideal for retail application

**5** 5 Years  
Standard Warranty

**7** 7 Years  
Extended Warranty

**500V**  
Surge Protection

**55/75/95/  
120mm**  
Cut-out





## General Specification

Voltage 220-240Vac  
50-60Hz  
CRI >80  
Life Time 50,000h  
Power Factor >0.95  
Ambient Temp -20°C to 45°C  
Housing Diecast aluminum



## Dimensions



Order Code	Power	Beam Angle	Finish	CCT	Lumen	Dimensions $\phi$ H
EDLDI5	5W	15/24/38°	White	6000K	<b>500lm</b>	$\phi$ 63*63mm
EDLDI10	10W	15/24/38°	White	6000K	<b>1000lm</b>	$\phi$ 63*78mm
EDLDI15	15W	15/24/38°	White	6000K	<b>1500lm</b>	$\phi$ 85*76mm
EDLDI20	20W	15/24/38°	White	6000K	<b>2000lm</b>	$\phi$ 85*93mm
EDLDI25	25W	15/24/38°	White	6000K	<b>2500lm</b>	$\phi$ 105*99mm
EDLDI30	30W	15/24/38°	White	6000K	<b>3000lm</b>	$\phi$ 105*115mm
EDLDI35	35W	15/24/38°	White	6000K	<b>3500lm</b>	$\phi$ 130*115mm