

Talio

Circular LED wall washer

- High performance CREE COB LED
- Negligible UV, ideal for retail application

5 5 Years
Standard Warranty

7 7 Years
Extended Warranty

500V
Surge Protection


75/95/115/120
145/175mm
Cut-out

General Specification

Voltage	220-240Vac 50-60Hz
CRI	>80
Life Time	50,000h
Power Factor	>0.95
Ambient Temp	-20°C to 45°C
Housing	Diecast aluminum



Dimensions



CHIP **OSRAM** LUMILEDS
 DRIVER **PHILIPS** LIFUD



Order Code	Power	Beam Angle	Finish	Dimensions ϕ H	CCT	Lumen
EWWDL09	9W	15/38°	White	ϕ 90*120mm	3000K 5000K	1020lm
EWWDL15	15W	15/38°	White	ϕ 105*120mm	3000K 5000K	1550lm
EWWDL25	25W	15/38°	White	ϕ 125*130mm	3000K 5000K	2550lm
EWWDL30	30W	15/38°	White	ϕ 140*130mm	3000K 5000K	3050lm
EWWDL40	40W	15/38°	White	ϕ 160*140mm	3000K 5000K	4100lm
EWWDL60	60W	15/38°	White	ϕ 190*160mm	3000K 5000K	5800lm

* Chrome & Silver factory order only