

Olive

Modular LED down light system

- Modular design of LED modules and housings
 - Low UGR LED modules available
- Color temperature switching 3000/4000/5000K
 - Each LED module has 2 wattage options

Wattage switching 

Modular design 

CHIP **OSRAM** LUMILEDS
 DRIVER **PHILIPS** LiFuD[®]



5 5 Years
Standard Warranty

7 7 Years
Extended Warranty

1000V
Surge Protection

**90/125/
160/200mm**
Cut-out

New Optional Gear



Standard/Self-test
universal emergency module
UEM II 

General Specification

Voltage	180-264Vac
	50-60Hz
CRI	>80
Life Time	50,000h
Power Factor	>0.90
Ambient Temp	-20°C to 50°C
Housing	Diecast aluminum



RoHS  

Order Code	Power	Beam Angle	Finish	CCT	Lumen	Dimensions D H
EDLO10	10W	90°	White	6000K	1000lm	φ105*38mm
EDLO15	15W	90°	White	6000K	1500lm	φ140*38mm
EDLO20	20W	90°	White	6000K	2000lm	φ140*38mm
EDLO30	30W	90°	White	6000K	3000lm	φ220*43mm
EDLO35	35W	90°	White	6000K	3500lm	φ220*43mm

* Where CCT switchable, colour temperature switches between 3000K, 4000K & 5000K

Dimensions

