

3 3 Years
Standard Warranty

5 5 Years
Extended Warranty

2000V
Surge Protection



Single, 4ft / 5ft / 6ft



Twin, 4ft / 5ft / 6ft

General Specification

Voltage 220-240Vac
50-60Hz
CRI >80
Life Time 50,000h
Power Factor >0.90
Ambient Temp -20°C to 50°C
Housing Polycarbonate



Evon

Non-corrosive integrated linear LED luminaire

- T8 non-corrosive LED replacement
- IP65 and vandal resistant (IK08)
- Optional built-in emergency module
- Optional built-in microwave sensor
- Opal diffuser
- 20mm Conduit entry

Wattage switching

Built-in emergency

Built-in motion sensor

Modular design

Ultra high efficiency

CHIP **OSRAM** **LUMILEDS**
DRIVER **PHILIPS** **LIFUD**



Order Code	Default	Alternative Power	Length	CCT	Lumen	Trade Price
EWP1210S4F	-	10W	4ft single	4000K	1350lm	
EWP1213S4F	-	13W	4ft single	4000K	1700lm	
EWP1216S4F	-	16W	4ft single	4000K	2100lm	
EWP1218S4F	18W	-	4ft single	4000K	2340lm	
EWP1220S4F	-	20W	4ft twin	4000K	2850lm	
EWP1226S4F	-	26W	4ft twin	4000K	3500lm	
EWP1232S4F	-	32W	4ft twin	4000K	4100lm	
EWP1236S4F	36W	-	4ft twin	4000K	4800lm	
EWP1518S4F	-	18W	5ft single	4000K	2450lm	
EWP1523S4F	-	23W	5ft single	4000K	3000lm	
EWP1526S4F	26W	-	5ft single	4000K	3500lm	
EWP1530S4F	-	30W	5ft single	4000K	4050lm	
EWP1534S4F	-	34W	5ft twin	4000K	4700lm	
EWP1544S4F	-	44W	5ft twin	4000K	5800lm	
EWP1552S4F	52W	-	5ft twin	4000K	6800lm	
EWP1560S4F	-	60W	5ft twin	4000K	7750lm	

Order Code	Power	Length	CCT	Lumen	Trade Price
EWP1840S4F	40W	6ft single	4000K	5000lm	
EWP1865S4F	65W	6ft twin	4000K	8125lm	

Options

Suffix	Description	Trade Price
/E	With integrated emergency module	
/S	Microwave sensor	
/ES	Emergency & Microwave sensor	

Battery

Order Code	Type	Capacity	Voltage	Trade Price
LFP7302-S20 (4ft, 5ft)	LiFePO4	2000mAh	6.4V	
EBAT2600 (6ft)	Li-ion	2600mAh	7.4V	

Dimensions

