

5 5 Years
Standard Warranty

7 7 Years
Extended Warranty

500V
Surge Protection

Jas

Slim IP65 bulkhead with integrated LED tray

- Switchable CCT (3000/4000/5000K)
- Choice of alternative decorative trims
- IP65 & vandal resistant (IK10)
- Integrated LED tray
- Option of base with emergency module
- Optional microwave sensor
- 20mm Conduit entry
- Conduit entries are not covered by the decorative rings

 CCT switching

 Built-in emergency

 Plug-in self-test EM

 Plug-in corridor sensor

 Interchangeable ring

 Flicker free

 Modular design


Anti-vandal Screw Pack
EPT-SCREW1


Anti-vandal Screw Driver
EPT-SCREWDRIVER1


Microwave Sensor
(Mounting height ≤8.5m)
EBTNLS1-MWS2

CHIP **OSRAM** LUMILEDS
DRIVER **PHILIPS** LIFUD®



Options
Eye


General Specification

Voltage 220-240Vac
50-60Hz
CRI >80
Life Time 50,000h
Power Factor 0.95
Ambient
Temp -20°C to 50°C
Housing Aluminium



RoHS **CE** 

Dimensions



Order Code	Power	CCT	Lumen	Trade Price
EBHDT12	12W	Switchable*	900lm(3000K) 1050lm(4000K) 1050lm(5000K)	
EBHDT20	20W	Switchable*	2000lm(3000K) 2050lm(4000K) 2050lm(5000K)	
EBHDT24	24W	Switchable*	2400lm(3000K) 2450lm(4000K) 2450lm(5000K)	

* When CCT switchable, colour temperature switches between 3000K, 4000K & 5000K