

3 3 Years
 Standard Warranty


5 5 Years
 Extended Warranty

500V
 Surge Protection

 Microwave Sensor
 (Mounting height ≤8.5m)
 EBTNLS1-MWS2

General Specification

 Voltage 220-240Vac
 50-60Hz
 CRI 84
 Life Time 50,000h
 Power Factor 0.92
 Ambient Temp -20°C to 50°C
 Housing Polycarbonate

Dimensions


Polo

Twist & Lock IP65 bulkhead with integrated LED tray

- Switchable CCT (3000/4000/5000K)
- Twist & lock ring for fast installation
- IP65 and vandal resistant (IK10)
- Integrated LED tray
- Option of base with emergency module
- Optional microwave sensor
- BESA box fitting points



CCT switching

Built-in emergency

Plug-in self-test EM

Plug-in corridor sensor

Flicker free

Modular design

 CHIP **OSRAM** LUMILEDS
 DRIVER **PHILIPS** LIFUD®

| Order Code | Power | CCT | Lumen | Trade Price |
|------------|-------|-------------|---------------|-------------|
| EBHFT12 | 12W | Switchable* | 1150lm(3000K) | |
| | | | 1260lm(4000K) | |
| | | | 1260lm(5000K) | |

* When CCT switchable, colour temperature switches between 3000K, 4000K & 5000K

Emergency Option

| Order Code | Description | Trade Price |
|-------------|---|-------------|
| EBHFT12/SCT | Standard emergency with LiFePO4 battery | |

Battery

| Order Code | Type | Capacity | Voltage | Trade Price |
|--------------|---------|----------|---------|-------------|
| EBAT2000LFP1 | LiFePO4 | 2000mAh | 3.2V | |

Optional Gears

| Type | Order Code | Description | Trade Price |
|----------------------------|--------------|--|-------------|
| Self-test Emergency module | EEC03LBL/S | Self-test emergency module, Li-ion battery | |
| Microwave Sensor | EBTNLS1-MWS2 | Microwave motion and daylight sensor | |