

# Badr

Low glare exterior wall-mount LED luminaire

**5** 5 Years  
Standard Warranty

**7** 7 Years  
Extended Warranty


**2000V**  
Surge Protection  
(L to GND)

CCT switching 

Dusk to dawn sensor 

- CCT switchable 3000K/4000K/6500K
  - Dusk to dawn sensor by default
- Die-cast Anti-corrosion aluminium body
  - IP65 and vandal resistant IK10
  - BESA box fitting points

CHIP **OSRAM** LUMILEDS  
DRIVER **PHILIPS** LIFUD®




65° x 90°

### General Specification

Voltage	220-240Vac 50-60Hz
CRI	> 80
Life Time	50,000h
Power Factor	> 0.95
Ambient Temp	-20°C to 50°C
Housing	Aluminium



### Dimensions



Order Code	Power	Beam Angle	CCT	Lumen	Trade Price
EWP12Q265	12W	65°x90°	Switchable*	1210lm(3000K)	
				1350lm(4000K)	
				1350lm(6500K)	
EWP20Q265	20W	65°x90°	Switchable*	2100lm(3000K)	
				2250lm(4000K)	
				2250lm(6500K)	

\* When CCT switchable, colour temperature switches between 3000K, 4000K & 6500K