

# Longo

Non-Corrosive linear luminaire with integrated LED

Plug-in emergency 

Plug-in corridor sensor 

CCT switching 

Modular design 

Ultra high efficiency 

- T8 non-corrosive LED replacement
- Switchable CCT (3000/4000/6000K)
  - Optional emergency module
- Optional microwave motion and daylight sensor with corridor dimming
- Durable and rugged IK10 polycarbonate construction
  - IP65
  - Suitable for through-wiring
  - Opal diffuser

CHIP **OSRAM** LUMILEDS  
DRIVER **PHILIPS** LIFUD®



**5** 5 Years  
Standard Warranty

**7** 7 Years  
Extended Warranty

**2000V**  
Surge Protection  
(L to GND)



Single, 4ft / 5ft



Twin, 4ft / 5ft



Microwave Sensor  
(Mounting height ≤8.5m)  
EBTNLS1-MWS2

## General Specification

Voltage 220-240Vac  
50-60Hz  
CRI >80  
Life Time 50,000h  
Power Factor 0.95  
Ambient Temp -20°C to 50°C  
Housing Polycarbonate



RoHS CE 

Order Code	Power	Length	CCT	Lumen	Trade Price
EWP1224S4	24W	4ft single	Switchable*	2650lm (3000K)	
				2900lm (4000K)	
				2900lm (6000K)	
EWP1236S4	36W	4ft twin	Switchable*	3950lm (3000K)	
				4350lm (4000K)	
				4350lm (6000K)	
EWP1548S4	48W	5ft single	Switchable*	4950lm (3000K)	
				5350lm (4000K)	
				5350lm (6000K)	
EWP1562S4	62W	5ft twin	Switchable*	6850lm (3000K)	
				7400lm (4000K)	
				7400lm (6000K)	

\* When CCT switchable, colour temperature switches 3000K, 4000K & 6000K

## Optional Gears

Type	Order code	Description	Trade Price
Emergency module	EEW05LBL/N	Emergency, with Li-ion battery	
Self-Test emergency module	EEW05LBL/S	Self-test emergency, with Li-ion battery	
Microwave Sensor	EBTNLS1-MWS2	Microwave motion and daylight sensor	

## Dimensions

