

Ivon

Non-corrosive integrated linear LED luminaire

Plug-in emergency

Built-in motion sensor

Modular design

Ultra high efficiency

- T8 non-corrosive LED replacement
 - IP65 and vandal resistant (IK08)
 - Emergency option
 - 20mm Conduit entry
- Options with microwave on/off sensor

CHIP **OSRAM** **LUMILEDS**
DRIVER **PHILIPS** **LIFUD**



Single, 4ft / 5ft / 6ft



Twin, 4ft / 5ft / 6ft

General Specification

Voltage	220-240Vac 50-60Hz
CRI	82
Life Time	50,000h
Power Factor	0.94
Ambient Temp	-20°C to 50°C
Housing	Polycarbonate



Order Code	Power	Length	CCT	Lumen	Trade Price
EWP1220S4F	20W	4ft single	4000K	2400lm	
EWP1230S4F	30W	4ft twin	4000K	3840lm	
EWP1530S4F	30W	5ft single	4000K	3840lm	
EWP1550S4F	50W	5ft twin	4000K	6630lm	
EWP1840S4F	40W	6ft single	4000K	5000lm	
EWP18650S4F	65W	6ft twin	4000K	8125lm	

Sensor option

Suffix	Description	Trade Price
/S	Microwave sensor	

Optional Gears

Type	Order code	Description	Trade Price
Emergency module	EEW05LBL/N	Emergency, with Li-ion battery	
Self-Test emergency module	EEW05LBL/S	Self-test emergency, with Li-ion battery	

Dimensions

