

Pico


High-power LED high mast floodlight

- Modular construction allows each module to be angled independently
- High efficiency of 160lm/W
 - IP66, IK09
 - High power 300W-1200W
- Multiple options for optics including asymmetric options


Flicker free 

Ultra high efficiency 


CHIP **OSRAM** **LUMILEDS**
DRIVER **PHILIPS** **MW**
MEAN WELL




20°



40°



60°



Asymmetric 50°

Order Code	Power	Beam Angle	Finish	CCT	Lumen	Trade Price
EFLD300Q	300W	20°/ 40° / 60° Asymmetric 50°	Grey	5000K	48000lm	
EFLD600Q	600W	20°/ 40° / 60° Asymmetric 50°	Grey	5000K	96000lm	
EFLD900Q	900W	20°/ 40° / 60° Asymmetric 50°	Grey	5000K	144000lm	
EFLD1200Q	1200W	20°/ 40° / 60° Asymmetric 50°	Grey	5000K	192000lm	

1-10V (standard) DALI / Photocell / DMX512 as special order

5 Years
Standard Warranty

7 Years
Extended Warranty

10000V
Surge Protection
(L to GND)

100-277V
Input voltage

General Specification

Voltage 100-277Vac
50-60Hz
CRI >70
Life Time 54,000h
Power Factor 0.96
Ambient Temp -30°C to 55°C
Housing Power coated aluminum



Dimensions

