

Cix

High power LED streetlight

- IP65 & IK10 protection
- Whole structure heat dissipation
- Ready for connection of photocell sensor wide choice of optics and installation.
 - Efficiency of 130lm/W
 - 3000K-6000K colour temperature

Plug-in photocell sensor 

Ultra high efficiency 

CHIP **OSRAM** 
DRIVER **PHILIPS** 



- 5** 5 Years Standard Warranty
- 7** 7 Years Extended Warranty
- 10000V** Surge Protection



General Specification

Voltage	220-240Vac 50-60Hz
CRI	>70
Life Time	50,000h
Power Factor	0.98
Ambient Temp	-40°C to 50°C
Housing	Diecast aluminum



Order Code	Power	CCT	Lumen	Dimensions L W H
ESTL50HH2	50W	4000K	6500lm	623*255*170mm
ESTL80HH2	80W	4000K	10400lm	666*295*170mm
ESTL100HH2	100W	4000K	13000lm	666*295*170mm
ESTL150HH2	150W	4000K	19500lm	736*315*170mm
ESTL200HH2	200W	4000K	26000lm	747*355*170mm
ESTL240HH2	240W	4000K	31200lm	747*355*170mm
ESTL300HH2	300W	4000K	39000lm	846*355*170mm

Dimensions

