

ELETI
 LIGHT

5 5 Years
 Standard Warranty

7 7 Years
 Extended Warranty

10000V
 Surge Protection
 (L to GND)


**110
240** 110-240V
 Input voltage


General Specification

Voltage	100-240Vac 50-60Hz
CRI	>70
Life Time	50,000h
Power Factor	0.95
Ambient Temp	-40°C to 50°C
Housing	Diecast aluminum
Connection	650 mm H05RN-F 3 x 1.0 mm ²



Dimensions



Tuna

LED street light for public areas

- Suitable for pole mounting (42±2 or 60±5mm pole)
- IP65 & IK10 rated
- Efficiency of 130lm/W
- 3000K-6000K colour temperature
- Option of photocell sensor
- Whole structure heat dissipation

Built-in photocell sensor

Ultra high efficiency

 CHIP **OSRAM** **LUMILEDS**
 DRIVER **PHILIPS** **MW**
MEAN WELL


Order Code	Power	CCT	Lumen	Dimensions L W H
ESTL50LH1	50W	4000K	6500lm	520*2212*90mm
ESTL100LH1	100W	4000K	13000lm	616*250*186mm
ESTL150LH1	150W	4000K	19500lm	677*303*186mm
ESTL200LH1	200W	4000K	26000lm	850*366*198mm